

**CLAIMS**

What is claimed is:

1. A transistor circuit for implementing a switch, comprising:
  - 5 a first switch node configured to connect to an external circuit;
  - a second switch node configured to connect to the external circuit;
  - a transistor device having a first terminal electrically communicating with the first switch node, a second terminal connected to the second switch node, and a third terminal configured to receive a control signal that controls the electrical connectivity
  - 10 between the first terminal and the second terminal;
  - a third switch node for receiving the control signal; and
  - a circuit connected to the third switch node and the third terminal of the transistor device, the circuit having an impedance configured to reduce the parasitic capacitance of the transistor device.
- 15 2. The circuit of claim 1, wherein the transistor device is a metal-oxide-semiconductor field-effect transistor.
3. A transistor circuit for implementing a switch, comprising:
  - 20 a first switch node configured to connect to an external circuit;
  - a second switch node configured to connect to the external circuit;
  - a transistor device having a first terminal connected to the first switch node, a second terminal connected to the second switch node, and a third terminal configured to receive a control signal for controlling the electrical connectivity between the first
  - 25 terminal and the second terminal; and
  - a circuit connected to the second terminal of the transistor device, the circuit configured to provide a voltage to the second terminal when the control signal engages the transistor device.

4. The circuit of claim 3, wherein the transistor device is a metal-oxide-semiconductor field-effect transistor.

5. The circuit of claim 3, wherein the circuit is an inverter circuit.

5

6. A transistor circuit for implementing a differential switch, comprising:

a first switch node configured to connect to an external circuit;

a second switch node configured to connect to the external circuit;

a first transistor device having a first terminal connected to the first switch  
10 node, a second terminal, and a third terminal configured to receive a control signal  
that controls the electrical connectivity between the first terminal and the second  
terminal;

a second transistor device having a first terminal connected to the third  
terminal of the first transistor device, a second terminal connected to the second  
15 switch node, and a third terminal configured to receive the control signal; and

a third transistor device having a first terminal connected to the first terminal  
of the first transistor device, a second terminal connected to the second terminal of the  
second transistor device, and a third terminal configured to receive the control signal.

20 7. The transistor circuit of claim 6, wherein the first transistor device, the second  
transistor device, and the third transistor device are each a metal-oxide-semiconductor  
field-effect transistor.

8. The circuit of claim 6, wherein the first transistor, the second transistor, and  
25 the third transistor are configured in a predetermined manner so that the parasitic  
characteristics of the first transistor, the second transistor, and the third transistor  
result in the transistor circuit having predetermined parasitic characteristics.